

## UHF RFID Fixed Type Reader (NL-RF2200)



### Performance Characteristics

<b>Supported Protocols</b>	ISO 18000-6 Type-C, EPC Class 1 Gen.2
<b>Frequency</b>	KCC
<b>Serial Interface Parameters</b>	115200 bps default, 8 data bits, no parity, 1 stop bits
<b>Ethernet Interface</b>	100Mbps – RJ45 Connector
<b>Power Consumption</b>	Active Current < 2A
<b>RF Output Power</b>	30 dBm
<b>Antenna Interface</b>	4-Ports
<b>Electrical Power</b>	5V DC

### Physical Characteristics

<b>Dimensions(LxWxT)</b>	107 mm x 98mm x 35,5mm
<b>Weight</b>	440 g

### ISO 18000-6 Type-C (EPC Gen.2) Characteristics

<b>Modulation</b>	PR-ASK
<b>Encoding method</b>	Miller
<b>Modulation Depth</b>	90% ~ 100 %

[www.nesslab.com](http://www.nesslab.com)

4th Floor, FYD Blds., 489-2 MaeTan 3-Dong, YeongTong-Gu, SuWon-City KyeongGi-Do 443-830, Korea

Tel: +82-31-206-1782 Fax: +82-31-206-1780