

For the hospitals of tomorrow



WS2

An all-in-one hygienic 2-inch compact printer
designed for patient safety

✓ KEY FEATURES & BENEFITS

- **Best in Class Patient Safety:** Disinfectant-ready, antimicrobial casing (industry-first feature)
- **Print on Demand** – High-quality patient ID wristbands and inpatient/laboratory labels. Compact, lightweight design for ease of transportation
- **Save Time** – Hassle-free media loading, enhanced printer setting tools and web browser for ease of operation. Faster than market average print speed, up to 7-inch/sec
- **Integrate Easily** – Cerner validated and ready for connection to all existing HIS/EMR hospital systems through the standard USB and Ethernet interfaces
- **Eradicate Errors** – Draw information from existing patient management systems
- **Multiple Printer Language Support** – Support of SZPL, SEPL and SDPL enables easy replacement of existing printer

WS2



Print wristbands and inpatient labels with one device

The WS2 is a hygienic, compact direct thermal desktop printer from SATO ideal for various healthcare scenarios. Suitable for direct use in the hospital ward due to its disinfectant-ready, antimicrobial plastic casing, the WS2 prints both patient ID wristbands and inpatient labels quickly and accurately for optimum patient safety and operator peace of mind.

The WS2 is also offered bundled with SATO patient ID wristbands as part of a competitive package, making the need to hand write labels a thing of the past.

✓ KEY TECHNICAL FEATURES

- USB/LAN connectivity as standard (IPv4/v6)
- Multiple printer utility setup
- Legacy Netbios/WINS compatibility
- Multiple emulation support (SZPL, SEPL and SDPL)
- Compatible with NiceLabel and BarTender label designer software
- Web browser settings
- Easy firmware update by USB memory



Patient safety is our priority

The compact size and light weight of the WS2 makes it easy to transport, giving operators the flexibility to print from desks and patient bedsides as required. SATO understands that space is at a premium in the hospital environment and the 2-inch WS2 has been specifically designed with this in mind. The device is up to 23% smaller than equivalent competitor models. In addition, the pure white body of the device and disinfectant ready, antimicrobial plastic casing enables hospital staff to keep the device clean and limit the contamination risk.

A key frustration for hospital staff is when multiple devices are required to print wristbands and labels. Over 50% of our customers say that they would prefer an easy to use, compact device that can support both wristband and inpatient label requirements.





Making the switch is simple

The SATO WS2 printer is easily integrated in to existing HIS/EMR hospital systems and is validated by Cerner for use in its systems. Users can control and configure the device with its dedicated setting tool, as well as via web browser.

The user-friendly features of the setting tool include a printer search, to find all connected printers for quick access and configuration, and multi LAN to simultaneously configure a range of printers on the network. The device is also compatible with the legacy WINS to connect to a remote network by using its NetBIOS name. Once set up, the WS2 is extremely simple to operate, even for the first-time user.

Although the WS2 is optimised to work with SATO wristbands for the highest-quality print, it is also compatible with most comparable wristband and label consumables currently available in the market. So, there's no need to worry about using your existing consumables supply before switching to SATO wristbands and labels.

WS2 — The smart choice for sustainability

Media replacements in wristband and label printers – for example, from adult to infant ID wristbands – can typically result in wasted media during calibration. This is not the case with the WS2, which is ready to print from the first label every time. The advantages of this are twofold, saving time and effort for hospital employees and reducing waste and overall carbon footprint for the hospital.

✓ KEY FIGURES

- 23% smaller than equivalent models on the market
- Faster than average 7-inch/sec print speed
- Lightweight at only 1kg
- High-quality 203dpi & 300dpi print resolutions available

COMPATIBLE WITH:

- ✓ Patient ID wristbands (optimised for SATO patient ID wristbands)
- ✓ Drug administration labels
- ✓ Histology sample labels
- ✓ Blood collection/transfusion labels
- ✓ Inpatient meal labels & all other types of 2-inch labels



WS2 Technical Specifications

Model			WS208	WS212
Print Specifications				
Print Method			Direct Thermal	
Print Resolution			8 dots/mm (203dpi)	12 dots/mm (300dpi)
Print Speed			2, 3, 4, 5, 6, 7 inches/sec (50, 76, 101, 127, 152, 177 mm/sec) 2 & 3ips for Peeler(Dispenser) Mode	2, 3, 4, 5 inches/sec (50, 76, 101, 127 mm/sec) 2 & 3ips for Peeler(Dispenser) Mode
Max. Print Area (Width x Length)			54.1mm x 2,540mm	56.8mm x 1,270mm
CPU			32 Bit RISC-CPU	
Printer Memory			Standard Memory (Flash ROM): 16 MB User Memory: 8 MB Standard Memory (SDRAM): 32 MB	
Media Specifications				
Sensor Type			Movable Reflective Sensor (I-Mark), Transmissive sensor (Gap)	
Media	Thickness		0.06 to 0.2mm (0.0024" to 0.0079") *Not applicable for wristbands	
	Shape	Winding Direction	Roll stock (Face-in, Face-out), Fan-fold	
		Max. Inner & Outer Diameter	5"(127mm) OD on a 1" (25.4 mm) / 1.5" (38 mm) ID core 4.5"(115mm) OD on a 0.5" (12.7mm) ID core	
	Max. Size		Width: 12mm~60mm Length 10mm~2,540mm *Min. Length: 25mm for Cutter / Peeler (Dispenser) Options	Width: 12mm~60mm Length 10mm~1,270mm *Min. Length: 25mm for Cutter / Peeler (Dispenser) Options
Fonts / Symbolologies				
Font			Bitmap Support Fonts of SZPL, SEPL, SDPL	
Barcode	1D Barcode		Code 39, Code 93, Code 128 (ISBT128), CODABAR (NW-7), EAN8/13, GS1 DataBar™, GS1-128 (UCC/EAN128), Interleaved 2/5, Industrial 2/5, JAN8/13, Matrix 2/5, MSI, POSTNET™, UPC-A/E	
	2D Barcode / Composite Symbols		PDF417, Micro PDF, Maxi Code, GS1 Data Matrix, Data Matrix (ECC200), QR Code, Composite Symbolologies, Aztec	
Print Direction			0°, 90°, 180°, 270° rotation per each data is available	
Communication Interfaces				
Interfaces			USB hosts (Type A) for Firmware Update, USB device (Type B) Fast Ethernet supporting: (IPv4/IPv6, WINS/Netbios)	
Printing Command			SZPL, SEPL, SDPL	
Operating Characteristics				
Power requirements	AC Adaptor		Voltage: AC 100 V ~ 240 V ± 10 % (full range) Frequency: 50 Hz - 60 Hz ± 5 %	
Environment	Operating		5 °C ~ 40 °C(41°F~104°F) / 25 %RH ~ 85 %RH (non-condensing)	
	Storage		-20 °C ~ 60 °C(4°F~140°F) / 10 %RH ~ 90 %RH (non-condensing)	
Dimensions			W 116 mm x H 170 mm x D 215 mm	
Weight			1 kg / 2.2 lbs	
Miscellaneous				
Anti-microbial Finishing			Disinfectant-ready Anti-microbial Casing	
Regulatory Approvals			FCC, cTUVus, CB, CE Marking, RCM	
Certification			Cerner Validated	
Options			Cutter, Peeler (Dispenser)	
Printer Driver			Windows Driver, BarTender®, NiceLabel®	

For more information about SATO in the Asia Pacific,
scan QR code below or [click here](#) to visit our website.



Version: Feb 2019 Rev. A

©2019 SATO Global Business Services Pte. Ltd. All rights reserved. Specifications subject to change without notice. Any unauthorized reproduction of the contents of this presentation, in part or whole, is strictly prohibited. SATO is a registered trademark of SATO Holdings Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.



WS2

For the hospitals of tomorrow | An all-in-one hygienic 2-inch compact printer designed for patient safety