

# XD3-40 시리즈

4인치 데스크톱 라벨 프린터



유통



창고관리



병원·약국



우편·택배

## 내구성과 실용성 겸비



XD3-40d



XD3-40t



### 믿을 수 있는 성능

- 감열식(XD3-40d), 열전사방식(XD3-40t) 라벨 인쇄 지원
- 5ips (127mm/sec) 인쇄속도 지원
- 203 dpi 해상도
- Stand Alone 기능 지원
- 언어 자동 변환



### 사용자 친화적인 디자인

- 조절가능한 용지 가이드 및 홀더로 편리한 용지교체
- 세팅이 편리한 용지 센서
- 필러, 외장 라벨 거치대 옵션
- 손쉬운 롤러 및 프린터 헤드 교체
- 하프인치와 풀인치 리본코어 사용 지원 (길이 74m 또는 300m)



### 다양한 인터페이스

- 표준 : USB
- 옵션 : USB + 시리얼 + 이더넷

# XD3-40 시리즈

## 4인치 데스크톱 라벨 프린터

### Specifications

#### Printer Specifications

##### Print Method

XD3-40d : Direct Thermal  
XD3-40t : Thermal Transfer or  
Direct Thermal

##### Print Speed

Up to 5 ips (127 mm/sec)

##### Print Resolution

203 dpi

##### Print Width

Up to 104 mm

##### Print Length

Up to 1,000 mm

##### Sensor

Transmissive(Fixed), Reflective(Adjustable),  
Ribbon-End (XD3-40t), Head Open

#### Media Characteristics

##### Media Type

Gap, Black Mark, Notch, Continuous,  
Fan-Fold

##### Media Width

15 ~ 118 mm

##### Media Roll Diameter

Up to 127 mm

##### Media Thickness

0.06 ~ 0.20 mm

##### Supply Method

Easy Paper Loading

##### Inner Core

25.4 ~ 38.1mm

#### Ribbon Characteristics

##### Ribbon Type

Wax, Wax / Resin, Resin, Outside

##### Ribbon Width

33 ~ 110mm

##### Ribbon Length

Up to 300m

##### Core Inner Diameter

25.4 mm, 12.7 mm

#### Physical Characteristics

##### Dimensions (WxDxH)

XD3-40d : 181 x 222 x 168 mm  
(7.13 x 8.74 x 6.62 inch)  
XD3-40t : 210 x 284 x 186 mm  
(8.3 x 11.2 x 7.3 inch)

##### Weight

XD3-40d : 1.7kg (3.75 lbs.)  
XD3-40t : 2.6kg (5.73 lbs.)

##### Electrical

EnergyStar Certified,  
External Power Adaptor 100-240V AC,  
50/60Hz

#### Performance Characteristics

##### Memory

64 MB SDRAM, 128 MB Flash

##### Interface

Standard: USB  
Optional: USB + Serial + Ethernet

##### Real Time Clock

Not Supported

#### Environment Characteristics

##### Temperature

Operating: XD3-40d: 0 ~ 40°C (32 ~ 104°F)  
XD3-40t: 5 ~ 40°C (41 ~ 104°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

#### Software

##### Emulation

SLCST<sup>™</sup>, BPL-Z<sup>™</sup> (ZPLII), BPL-E<sup>™</sup> (EPL)

##### Driver / Utility

Windows Driver (Europlus / Seagull)  
Linux / Mac CUPS Driver  
Virtual COM USB / Ethernet Driver  
Utility Program  
OPOS Driver  
Bartender Ultralite for BIXOLON  
Label Artist-II<sup>™</sup>

##### SDK / Plugin

Windows SDK, Linux SDK

#### Fonts / Graphics / Symbolologies

##### Fonts

Bitmap Fonts (SLCS, BPL-Z, BPL-E) /  
Scalable Fonts (SLCS, BPL-Z) /  
Unicode supported  
(UTF-8, UTF-16LE, UTF-16BE)

##### Graphics

Supporting user-defined fonts, graphics,  
formats and logos

##### Barcode Symbolologies

1D: Codabar, Code 11, Code 39, Code 93,  
Code 128, EAN-13, EAN-8,  
Industrial 2-of-5, Interleaved 2-of-5,  
Logmars, MSI, Plessey, Postnet,  
GS1 DataBar (RSS-14), Standard 2-of-5,  
UPC/EAN extensions, UPC-A, UPC-E,  
IMB  
2D: Aztec, Codablock, Code49, Data Matrix,  
MaxiCode, MicroPDF417, PDF417,  
QR Code, TLC39

#### Accessories

##### Standard

Cable-USB

##### Optional

Peeler, External Paper Supply

